

**AMENDMENTS TO THE CLAIMS**

1. **(Currently Amended)** A system for receiving audio signals from a plurality of microphones and transferring said audio signals via a common composite signal channel to a receiving unit, said system comprising:

at least two satellite units, each having a separate housing, a microphone signal input, a composite signal channel input, and summing means for summing a microphone signal and a composite signal; and

a master unit having a composite signal channel input, and signal converting means for converting a composite signal into a master signal, which is provided to the receiving unit via a master signal output; wherein

each satellite unit is positionable away from the receiving unit and connected to said common composite signal channel, such that the microphone signal received at the respective satellite unit, is added to said composite signal, which is fed to the master unit; and

wherein said master unit is arranged to supply operating power to the satellite units and  
said system comprises at least two common composite signal channels.

2. (Original) The system as claimed in claim 1, wherein at least one of said satellite units comprises a composite signal channel input and a composite signal channel output, and wherein

the composite signal output of a first satellite unit is connected to the composite signal channel input of the master unit;

the composite signal output of a second satellite unit is connected to the composite signal input of the first satellite unit; and

signals received at the composite signal input and at the microphone signal input of the respective satellite unit are added by the respective summing means and provided at the composite signal output.

3. (Original) The system as claimed in claim 1, wherein at least one of said satellite units has one composite signal channel connector, which via a T-connector is connected to said common composite signal channel.

4. (Original) The system of claim 3, wherein said composite signal channel connector is connected to said T-connector via a cable.

5. Canceled.

6. (**Currently Amended**) The system as claimed in claim 5 1, wherein each satellite unit comprises at least two microphone inputs, which are connected to a respective common composite signal channel.

7. (Original) The system as claimed in claim 6, wherein each satellite unit comprises panning control means for controlling the panning of the microphones.

8. (Original) The system as claimed in claim 1, wherein each satellite unit comprises level control means for controlling the level of the signal from the microphone input.

9. (Original) The system as claimed in claim 8, wherein said level control means comprises an attenuation control.

10. (Original) The system as claimed in claim 8, wherein said level control means comprises a gain control.

11. (Original) The system as claimed in claim 1, wherein said summing means comprise a superposition circuit, arranged to superpose the microphone signal onto the composite signal.

12. (Original) The system as claimed in claim 1, wherein said summing means comprise a summing circuit.

13. (Original) The system as claimed in claim 12, wherein said summing circuit is an analog summing circuit.

14. (Original) The system as claimed in claim 12, wherein said summing circuit is a digital adding circuit.

15. (Original) The system as claimed in claim 1, wherein said converting means comprise an amplifier circuit.

16. (Original) The system as claimed in claim 1, wherein said converting means comprise a transformer.

17. (Original) The system as claimed in claim 1, wherein said converting means comprise an electronic balancing circuit.

18. (Original) The system as claimed in claim 13, wherein said master signal is an audio signal adapted for standard mixing console inputs.

19. **(Currently Amended)** A system for receiving audio signals from a plurality of microphones and transferring said audio signals via a common composite signal channel to a receiving unit, said system comprising:

at least two satellite units, each having a separate housing, a microphone signal input, a composite signal channel input, and summing means for summing a microphone signal and a composite signal; and

a master unit having a composite signal channel input, and signal converting means for converting a composite signal into a master signal, which is provided to the receiving unit via a master signal output; wherein

each satellite unit is positionable away from the receiving unit and connected to said common composite signal channel, such that the microphone signal received at the respective satellite unit, is added to said composite signal, which is fed to the master unit; and said master unit is arranged to supply operating power to the satellite units and, ~~wherein the said~~ receiving unit is a mixing console.

20. (Previously Presented) A system for receiving audio signals from a plurality of microphones and transferring said audio signals via a common composite signal channel to a receiving unit, said system comprising:

at least two satellite units, each having a microphone signal input, a composite signal channel input, and summing means for summing a microphone signal and a composite signal; and

a master unit having a composite signal channel input, and signal converting means for converting a composite signal into a master signal, which is provided to the receiving unit via a master signal output; wherein

each satellite unit is connected to said common composite signal channel, such that the microphone signal received at the respective satellite unit, is added to said composite signal, which is fed to the master unit;

said system comprises at least two common composite signal channels; and

first and second master signals are supplied from the master unit to the receiving unit via first and second connectors and wherein the receiving unit, via at least one of said first and second connectors, supply operating power to at least the master unit.

21. (Original) The system as claimed in claim 20, wherein said first connector is arranged to receive operating power, which is supplied to at least the master unit and said second connector is arranged to receive operating power, which is supplied to the satellite units as microphone operating power.

22. (Original) The system as claimed in claim 21, wherein said microphone operating power is one of a bias voltage and a phantom power.

23. (Previously Presented) The system as claimed in claim 1, wherein said master unit and said satellite units are contained in a separate housing, and wherein said master unit and satellite units are interconnected by cables.

24. (Original) The system as claimed in claim 1, wherein said satellite units are arranged near a respective microphone, and said master unit is arranged near said satellite unit.

25. Canceled.

26. **(Currently Amended)** ~~The master unit as claimed in claim 25~~ A master unit for use in a system for receiving audio signals from a plurality of microphones and transferring said audio signals via a common composite signal channel to a receiving unit, said system comprising:

at least two satellite units, each having a separate housing, a microphone signal input, a composite signal channel input, and summing means for summing a microphone signal and a composite signal; and

a master unit having a composite signal channel input, and signal converting means for converting a composite signal into a master signal, which is provided to the receiving unit via a master signal output; wherein

each satellite unit is positionable away from the receiving unit and connected to said common composite signal channel, such that the microphone signal received at the respective

satellite unit, is added to said composite signal, which is fed to the master unit; and wherein said master unit is arranged to supply operating power to the satellite units, said master unit comprising including:

a composite signal input connector for receiving a composite signal from a plurality of separately housed satellite units;

signal converting means for converting the composite signal into a master signal, and

a master signal output connector for providing said master signal to a receiving unit;  
wherein and said master signal output connector comprises first and second connectors, wherein said first connector is arranged to provide a first signal channel to the receiving unit and to receive operating power for at least the master unit, and wherein said second connector is arranged to provide a second signal channel to the receiving unit and to receive operating power for the satellite units.

27. Canceled.

28. **(Currently Amended)** ~~The satellite unit as claimed in claim 27~~ A satellite unit for use in a system for receiving audio signals from a plurality of microphones and transferring said audio signals via a common composite signal channel to a receiving unit, said system comprising:

at least two satellite units, each having a separate housing, a microphone signal input, a composite signal channel input, and summing means for summing a microphone signal and a composite signal; and

a master unit having a composite signal channel input, and signal converting means for converting a composite signal into a master signal, which is provided to the receiving unit via a master signal output; wherein

each satellite unit is positionable away from the receiving unit and connected to said common composite signal channel, such that the microphone signal received at the respective satellite unit, is added to said composite signal, which is fed to the master unit; and said master unit is arranged to supply operating power to the satellite units, said satellite unit including:

a composite signal channel connector for receiving a composite signal;  
a microphone input connector for receiving a microphone signal, and  
summing means for summing said composite signal and said microphone signal, wherein  
and said composite signal channel connector is adapted for receiving microphone operating power.

29.-30. Canceled.

31. (Previously Presented) The system as claimed in claim 1, wherein said master unit and at least one of said satellite units are interconnected by a first cable.

32. (Previously Presented) The system as claimed in claim 31, wherein said composite signal channel is arranged to be propagated between the satellite unit and the master unit by said first cable.

33. (Previously Presented) The system as claimed in claim 31, wherein said first cable is arranged to propagate said composite signal channel and said operating power.

34. (Previously Presented) The system as claimed in claim 31, wherein said at least two satellite units are interconnected by a second cable.

35. (Previously Presented) The system as claimed in claim 34, wherein said composite signal channel is arranged to be propagated between said satellite units by said second cable.

36. (Previously Presented) The system as claimed in claim 34, wherein said second cable is arranged to propagate said composite signal channel and said operating power between said satellite units.

37. Canceled.